



A new range of reciprocating compressors
with a 3-year guarantee*



⇒ SILPACK
Silenced reciprocating
compressors

INTELLIGENT AIR TECHNOLOGY

SILpack compressors offer an alternative for applications where low noise is essential.



Type	Power HP	Power supply	Flow rate m ³ /h	Receiver litres	Pressure bar	Noise level dB(A)	Cast iron cylinder	Rotation speed r.p.m.	Connection diameter	Weight kg	Dimensions mm
------	----------	--------------	-----------------------------	-----------------	--------------	-------------------	--------------------	-----------------------	---------------------	-----------	---------------

⇒ WITH BUILT-IN 24 LITRE RECEIVER

SILpack R 242	2	230V single phase	10	24	8	66	1	2450	1/4"	70	490x690x610
---------------	---	-------------------	----	----	---	----	---	------	------	----	-------------

⇒ SILENCED UNITS

SILpack R 335T	5.5	400 3 phase delta-delta	30	0	10	68	2 Two stage	1400	1/2"	120	837x592x735
SILpack R 477T	7.5	400 3 phase delta-delta	43	0	10	66	2 Two stage	1000	1/2"	153	837x592x735
SILpack R 477Y	7.5	400Tri E/T	43	0	10	66	2 Two stage	1000	1/2"	153	837x592x735
SILpack R 630T	10	400 3 phase delta-delta	59	0	10	68	2 Two stage	980	1/2"	173	837x592x735
SILpack R 630Y	10	400Tri E/T	59	0	10	68	2 Two stage	980	1/2"	173	837x592x735

⇒ 12 BAR SILENCED UNITS

SILpack R 335T 12	5.5	400 3 phase delta-delta	24	0	12	68	2 Two stage	1180	1/2"	120	837x592x735
SILpack R 477T 12	7.5	400 3 phase delta-delta	37	0	12	66	2 Two stage	920	1/2"	153	837x592x735
SILpack R 477Y 12	7.5	400 Tri E/T	37	0	12	66	2 Two stage	920	1/2"	153	837x592x735
SILpack R 630T 12	10	400 3 phase delta-delta	51	0	12	66	2 Two stage	850	1/2"	173	837x592x735
SILpack R 630Y 12	10	400 Tri E/T	51	0	12	66	2 Two stage	850	1/2"	173	837x592x735

⇒ SILENCED RECEIVER-MOUNTED UNITS

SILpack R 294/270T	4	400 3 phase delta-delta	21.8	270	10	68	2	1470	1/2"	200	1440x1220x592
SILpack R 335/500T	5.5	400 3 phase delta-delta	30	500	10	68	2 Two stage	1400	1/2"	215	2000x1330x600
SILpack R 477/500T	7.5	400 3 phase delta-delta	43	500	10	66	2 Two stage	1090	1/2"	273	2000x1330x600
SILpack R 477/500Y	7.5	400Tri E/T	43	500	10	66	2 Two stage	1090	1/2"	273	2000x1330x600
SILpack R 630/500T	10	400 3 phase delta-delta	59	500	10	68	2 Two stage	980	1/2"	295	2000x1330x600
SILpack R 630/500Y	10	400Tri E/T	59	500	10	68	2 Two stage	980	1/2"	295	2000x1330x600

⇒ SILENCED RECEIVER-MOUNTED UNITS, WITH INTEGRATED DRYERS

SILpack RF 294/270T	4	400 3 phase delta-delta	21.8	270	10	68	2	1470	1/2"	230	1440x1220x592
SILpack RF 335/500T	5.5	400 3 phase delta-delta	30	500	10	68	2 Two stage	1400	1/2"	245	2000x1330x600
SILpack RF 477/500T	7.5	400 3 phase delta-delta	43	500	10	66	2 Two stage	1090	1/2"	303	2000x1330x600
SILpack RF 477/500Y	7.5	400Tri E/T	43	500	10	66	2 Two stage	1090	1/2"	303	2000x1330x600
SILpack RF 630/500T	10	400 3 phase delta-delta	59	500	10	68	2 Two stage	980	1/2"	325	2000x1330x600
SILpack RF 630/500Y	10	400Tri E/T	59	500	10	68	2 Two stage	980	1/2"	325	2000x1330x600

SILpack R low-noise compressors

- Cast iron cylinder
- Bi cylinders
- Two stage (except SILpack R 242)
- Belt drive
- Low speed
- Low noise level
- Receiver-mounted version
- Receiver-mounted version with integrated refrigeration dryer, filter and by-pass
- Filled with CompAir CLS 2000 synthetic compressor oil which improves performance, lubrication, cooling and the mechanical strength of the unit

INTELLIGENT AIR TECHNOLOGY

* on the compression element



INTERNET:
www.compair.com
sales@compair.com



CompAir Policy is one of continuous improvement and we therefore reserve the right to alter specification and prices without prior notice. All products are sold subject to the Company's conditions of sale.